



Eclipse is an R&D house specialising in live-broadcast equipment. Everything is designed, created and produced by accomplished and acclaimed engineers, all of whom possess extensive knowledge and understanding of using equipment out in the field. This means that from inception, all products are designed in a practical, perceptive and intelligent manner and every aspect of the design is focused on the user and its operating environment. Eclipse equipment is already successfully used by leading Broadcasters but it's also regularly used by the team that design it. A team who are continually developing and improving the technology in order to meet the constantly evolving landscape of live-broadcasting.

FIBRE OPTIC

Fibre Optic Tranciever

Lyme Single Channel Fibre Optic
Tranceiver kit - LED interface

Overview

The Lyme fibre optic transmitter and receiver kit is designed to take a Digital Video Source on BNC and transmit it via Fibre optic cable to the receiver. (FC Connection, others available on request, contact us for details)

Each unit also has an array of LED's for diagnostic purposes, this will allow the user to determine the status of the incoming Video Signal, the transmit level of the TX Unit and the receive level at the RX unit (so determining whether the fibre is in good condition and clean).

Each unit also features a Reclocker, although this can easily be disabled as required in some specific circumstances.

It is also possible to output an alarm signal via pins 2 & 3 on the 4 pin power XLR socket. This could, for example, be connected to a remote lamp near the Vision Guarantee's position, to provide a visual warning of any problems.

Power requirements is 7-17V DC via 4 pin xlr connectors.

All of the products in the range have been created using high quality components and materials, arguably the best available on the commercial market, making them robust, durable and dependable.



Technical details

- HD-SDI Input/Output via 1 x 75Ohm BNC
- Fibre levels displayed on a 6 LED Level Meter
- Optional Reclocker bypass in both units
- Supports SD, HD and 3D SDI at data rates of 270Mb/s, 1483.5 Mb/s, 1485 Mb/s, 2967Mb/s & 2970Mb/s
- Up to 30 Km range
- Enclosed within a strong snap-close enclosure, with two mounting points on the base
- SMPTE, DVB and ASI Compliant
- Power On LED
- Video-Lock LED is Tri Colour to indicate Signal Type

- Input Voltage is 7 - 17.5 VDC, 2W at 13.8V DC (4 pin XLR connector)
- Including Connectors
Dimensions are 150mm x 68mm x 41mm
- FC fibre connectors fitted as standard, ST and others available on request
- Configurable relay-trigger short output for alarm and/or fibre level warnings (pins 2 & 3 of power XLR)

Accepts the following Formats;

1080/60p, 1080/59.94p, 1080/50p, 1080/30p, 1080/29.97p, 1080/25p, 1080/24p, 1080/23.98p, 1080/60i, 1080/59.95i, 1080/50i, 1080/30psF, 1080/29.97psF, 1080/25psF, 1080/24psF, 1080/23.98psF, 720/60p, 720/59.94p, 720/50p, 720/30p, 720/29.97p, 720/25p, 720/24p, 720/23.98p